Actions, filters, triggers

- Implementing deprecated filtersImplemented and available filters
 - rbwc_customer_synchronize

Implementing deprecated filters

If you for some strange reason would like to implement filters that has been used in the old plugin, implementation should look like this. In this live example, you actually execute the deprecated filter before executing the up-to-date one. Doing this, you get the chance to inject old values on the way through the new filter.

```
$deprecatedStoreId = WordPress::applyFiltersDeprecated('set_storeid', null);
$storeId = (int)WordPress::applyFilters('setStoreId', $deprecatedStoreId);
```

Implemented and available filters

This plugin offers a bunch of internal filters and actions. Below is a list of them.

Filter name	Туре	In	Return	Description		
rbwe_ad min_dyna mic_cont ent	filter	\$cont ent \$curr ent_s ection	\$yourCont ont	Renders dynamic content for each section. If something specific, that is not included in the form fields, this could be used and will be appended in the of each section.		
rbwc_ord er_status _update	action	\$orde rld \$new Statu sSlug	Silent	Preferred as an action to fire up more features during callback status changes and manually updated statuses in the order admin. Will be used to run payment_completed() during finalized orders. If further actions is required, we or a developer can make use of this action. resurs_bank_order_status_update mentioned here, should be fired up separately in the same code area.		
rbwc_get _custom_ form_fields	filter	\$curr entAr ray	\$yourArray	If settings are dependent of other activated options in the configuration, this filter should be used. The plugin use this internally, to enable/disable the developer-options tab. For a code example, take a look at this commit.		
rbwc_get _plugin_i nformation	filter	\$cont ent	\$yourCont ent	Content added to this section will be shown other vital data for your platform, you should Example :	in the information/support, as a part of the "version view". If you for example need to show openssI releas d add it here.	
				['OpenSSL version' => 0	defined('OPENSSL_VERSION_TEXT') ? OPENSSL_VERSION_TEXT : ''	
				Plugin-version	0.0.1.0	
				Composer-version	0.0.1.0	
				PHP-Version	7.2.31-1+ubuntu18.04.1+deb.sury.org+1	
rbwc_can _display_ order_inf o_after_d etails	filter	boole an	boolean	rbwc_can_display_order_info_after_ <where> The can_display-trio is used to disable each payment info section in the admin view. The details section also has a separate action that triggers inste standard action from woocommerce. That action delivers all payment information required to recreate the "bluebox information" from v2.x.</where>		
rbwc_sho w_order_ details	action	\$orde rData	Is echo	This action is executed right after the rbwc_can_display_order_info_after_details-filter. By disabling the three can_display_order_info and execute hook with a full order representation, it is possible to create your own view right after the order details in the admin. This is pushed in here, in case the requires a different view from this plugin.		

rbwc_can _display_ order_inf o_after_b illing	filter	boole an	boolean	rbwc_can_display_order_info_after_ <where> The can_display-trio is used to disable each payment info section in the admin view.</where>	
rbwc_can _display_ order_inf	filter	boole an	boolean	rbwc_can_display_order_info_after_ <where> The can_display-trio is used to disable each payment info section in the admin view.</where>	
o_after_s hipping rbwc_get	filter	\$size,	integer	If you believe you need a shorter or longer value for the default payment field lenght, that is set to 24, you can apply for that value here.	
_payment _field_size	inter	\$field Name		in you believe you need a shorter or longer value for the delaut payment held length, that is set to 24, you can apply for that value here.	
rbwc_pref er_article _number _sku	filter	boole an	boolean	If you have further requirements of how article numbers are fetched, you could return true for this, to make the plugin use Sku instead - if it exis. This is not configurable through the admin interface as it is handled as a filter instead. If it is really necessary to use SKU, use this filter instead.	
rbwc_get _article_n umber	filter	\$curr entArt icleN umbe r, WC_ Produ ct	\$theArticle Number	If you have further ways of fetching an article from a WC_Product object, this is where you do it.	
rbwc_cou pons_ex_ tax	filter	boole an, WC_ Coup on	boolean	For special occasions when the options should remain untouched but we still need to make exceptions for coupons.	
rbwc_get _coupon_ vat_pct	filter	integ er	integer	Default value for vat percent in the coupon calculcation method is 0. Coupons are normally, at least in Sweden, already applied with vat.	
rbwc_get _address _disabled	filter	boole an	boolean	Disable getAddress form in checkout (where it is implementable).	
rbwc_js_l oaders_c heckout	filter	array	array	List of javascripts (frameworks?) that should be loaded during RCO.	
rbwc_get _shipping _name	filter	string	string	Generates own article number for shipping if the default "shipping" is not preferred, or if another translation is needed.	
rbwc_get _shipping _descripti on	filter	string	string	Generates a orderline description for the shipping, if the preferred translation for "Shipping" is not preferred.	
rbwc_get _fee_na me	filter	string	string	Generates own article number for payment fees, if the default "fee" is not preferred, or if another translation is needed.	
rbwc_get _fee_des cription	filter	string	string	Generates a orderline description for the fee, if the preferred translation for "Payment fee" is not preferred.	
rbwc_set _store_id	filter	string	string	Set a store id for the payment request.	
rbwc_trig ger_callb ack	filter	array	array	External code to handle test callbacks.	
rbwc_get _address _field_co ntroller	filter	array	array	getTransformedAddressResponse, ability to use other fields than the defaults, generated by the internal filter.	
rbwc_get _address _button_t ext	filter	string	string	Alternative naming or translation for the getAddress request button. Default is "Get address".	
resurs_tri gger_test _callback	filter	string	string	External trigger for the test callback. 2.X-DEPRECATED	
set_storeid	filter	string	string	Store id, old filter. 2.X-DEPRECATED	
resurs_g etaddress _enabled	filter	boole an	boolean	Sets, in the old fashioned way, a state if getAddress should be enabled where it is normally disabled. 2.X-DEPRECATED	
rbwc_ custo mer_s ynchr onize	trigger		-	Javascript frontend trigger. Used to synchronize customer billing/shipping fields. Event contains. depending on version.	

```
$('b ody'
).tr
igger
(
'rbw
c_cu
stom
er_s
ynch
roni
ze',
{

vers
ion:
2
})
```

When v1 is sending data

```
{
  version: 1
}
```

resursBankRcoDataContainer Version 1 sample data:

```
"rco_customer": {
               "paymentMethod": "INVOICE",
                "customerData": {
                      "address": {
                                "firstname": "Korv",
                               "surname": "Alexandersson",
                                "address": "Glassgatan 15",
                                "addressExtra": "",
                                "postal": "41655",
                                "city": "Göteborg",
                               "countryCode": "SE",
                               "telephone": "0701122334",
                                "email": "noreply@resurs.se"
                        "delivery": {},
                        "ssn": "198001010001",
                        "paymentMethod": "INVOICE"
        },
        "rco_payment": "INVOICE"
}
```

When v2 is sending data

```
{
  version: 1
}
```

resursBankRcoDataContainer Version 2 sample data (when deliveryAddress has content it looks similarly as billingAddress):

resursBankRcoDataContainer Version 2 { "rco_customer": { "type": "CustomerChangeEvent", "ts": 1632576948828, "source": "@rco-app", "phone": "0701122334", "email": "noreply@resurs.se", "billingAddress": { "firstName": "Vincent", "lastName": "Alexandersson", "addressRow1": "Glassgatan 15", "addressRow2": null, "postalCode": "41655", "city": "Göteborg" "deliveryAddress": { "firstName": null, "lastName": null, "addressRow1": null, "addressRow2": null, "postalCode": null, "city": null } }, "rco_payment": { "type": "PSP_DEBIT_CARD", "ts": 1632576948828, "source": "@rco-app", "method": "PSPCARD_DEBIT", "id": "PSPCARD_DEBIT", "fee": 0 } } Then ResursCheckout framework v1 or v2 rejects a payment, either because of a failure or a denied payment (v1 only), this trigger executes and can rbwc_pur trigger \$('b ody' chase_rej picked up by integrated plugins to handle a rejected order. ect 'rbw c_pu rcha se_r ejec t', { type : '< type >' }

rbwc_pur chase_rej ect_custo	filter	string	string	When Resurs Bank Checkout rejects a payment due to failure/deny, this filter adds an extra note to customer in a front-end message. The default loo below:	
mer_mes sage				<pre>\$failNote = sprintf(('Order was rejected by Resurs Bank with status %s.', 'trbwc'), \$rejectType);</pre>	
				The above message is always injected in order notices and in the default customer message. After this message has been added to the order, furthe added:	
				<pre>\$failNote .= ' ' . WordPress::applyFilters('purchaseRejectCustomerMessage', ('Please contact customer service for more information.', 'trbwc'));</pre>	
				The above "Contact customer service"-message is added with a filter setup (which is this). If you want to change this message, you can use the ment filter to update the string with your own.	
rbwc_get _payment _method _icon	filter	\$url, \$pay ment Meth odData	string	When logos are active for payment methods, you can customize the look of the icon by adding this filter. The output string should be a URL to your cologo. For each payment method. \$paymentMethodData contains details about type, specificType and id that is vital for method type detection. This also deprecates RWC-33 - Getting issue details STATUS	
rbwc_get _specific _type_fiel ds	filter	\$retur n (array), \$key	array	Customizable customer form fields for checkouts. See this section.	
rbwc_get _minimu m_annuit y_price	filter	\$inte ger, \$cust omer Count ry	integer	When annuity factors are handled, the minimum payment price is 150 SEK/DKK/NOK or 15 EUR for FI. If you really need to change this value to som lower, this is the filter to use.	
rbwc_part _payment _string	filter	string , ['curre ncy' => \$curr ency, 'mont hlyPri ce' => \$mon thlyPri ice, 'mont hlyDu ratio n, 'paym entLi mit' => \$mini mum Paym entLi mit 1	string	When displaying part payment information on product pages, the below string is set to be default. This filter executes an internal feature that makes it to show part payment information via a WordPress page. It also helps if you want to generate your own information without a page. The second varia filter is the the default values for duration and months. Currency is based on <code>get_wooccommerce_currency_symbol()</code> and follows the "wooccommerce currency ruleset". Undocumented shortcodes is some of the data that can be extracted from <code>getPaymentMethods</code> , starting with "method". For example, to <code>get</code> the id fourner payment method in the annuity factor setup you can use "[metodld]" or "[methodDescription]". Default text: Part pay from %s per month.	
rbwc_met hod_min_ limit	filter	int, \$pay ment Meth odInf ormat ion	int	If you want to limit the minimum allowed payment amount for a specific payment method, this is the one to set the data with. For example, you require payment amounts to be higher than 1000, to turn on the INVOICE, but the payment method allows payments from 500. The minAmount of the payment method can never be exceeded.	
rbwc_met hod_max _limit	filter	int, \$pay ment Meth odInf ormat ion	int	If you want to limit the maximum allowed payment amount for a specific payment method, this is the one to set the data with. For example, you require SWISH to not be higher than 10000 but the payment method allows payments up to 20000. The maxAmount of the payment method can never be exceeded.	

part_pay ment_rea d_more_ string	filter	string	string	Text to be shown in the installment sections (Defaults to 'Read more.', with translations in mind).
rbwc_set _curl_tim eout	filter	int	int	If you need to change the curl timeouts (for very slow connections) this gives you the value 12 by default, and this can be changed to a higher or low on demand. The timeouts are linked to ecom php communication with Resurs Bank.
rbwc_get _default_ country	filter	string	string	Default returns get_option('woocommerce_default_country') but can be changed on fly if this is very important for you.